

PRESTAZIONI ELETTROVENTILATORI - SERIE CPS/T
ELECTRICAL FANS PERFORMANCES - MODEL CPS/T

CPS/T

Tolleranza sulla portata ±5% - Capacity tolerance ±5% Tolleranza sulla rumorosità +3 dB(A) Noise level tolerance +3 dB(A)				Portata d'aria - Air capacity (m ³ /h)											
Ventilatore tipo Fan type	g/1' rpm	kW inst.	dB(A)	2400	2700	3000	3360	3780	4260	4800	5400	6000	6720	7500	8400
				Pressione totale - Total pressure (mm H2O)											
CPS/T 5,5	1440	4	68	-	180	178	175	170	165	160	155	145	135	115	98
CPS/T 7,5	1440	5.5	71	-	-	-	-	230	228	225	220	215	208	200	190
CPS/T 10	1450	7.5	73	-	-	-	-	-	-	-	250	250	245	240	230
CPS/T 15	1460	11	74	-	-	-	-	-	-	-	280	280	280	280	275
CPS/T 20	1460	15	76	-	-	-	-	-	-	-	-	-	-	315	315
CPS/T 30	1470	22	77	-	-	-	-	-	-	-	-	-	-	365	365
CPS/T 40	1470	30	80	-	-	-	-	-	-	-	-	-	-	-	-
CPS/T 50	1475	37	81	-	-	-	-	-	-	-	-	-	-	-	-
CPS/T 60	1475	45	83	-	-	-	-	-	-	-	-	-	-	-	-
CPS/T 75	1475	55	84	-	-	-	-	-	-	-	-	-	-	-	-

PRESTAZIONI ELETTROVENTILATORI - SERIE CPS/T
ELECTRICAL FANS PERFORMANCES - MODEL CPS/T

CPS/T

Portata d'aria - Air capacity (m³/h)

9600	10800	12000	13500	15000	16800	18900	21300	24000	27000	30000	33600	37800	42600	48000	54000
------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Pressione totale - Total pressure (mm H₂O)

75	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
175	150	125	-	-	-	-	-	-	-	-	-	-	-	-	-
220	210	190	-	-	-	-	-	-	-	-	-	-	-	-	-
265	255	240	215	190	160	125	-	-	-	-	-	-	-	-	-
310	300	290	280	265	240	210	175	-	-	-	-	-	-	-	-
365	360	350	335	320	305	290	250	210	-	-	-	-	-	-	-
-	400	400	395	390	375	360	345	325	300	265	-	-	-	-	-
-	450	450	445	435	425	410	395	370	340	310	265	200	-	-	-
-	-	-	-	500	495	490	480	460	440	415	390	350	-	-	-
-	-	-	-	570	565	555	540	525	505	485	460	430	375	325	220